

ADA 028084

APPLIED
RESEARCH
LABORATORIES

THE UNIVERSITY OF TEXAS
AT AUSTIN



ARL - YR - 76 - 31
5 July 1976

Copy No. 23

SUMMARY OF ENVIRONMENTAL ACOUSTIC DATA PROCESSING
Annual Report under Contract N00014-70-A-0166, Task 0016
1 July 1973 - 30 June 1974

Glen E. Ellis

OFFICE OF NAVAL RESEARCH
Contract N00014-70-A-0166, Task 0016



Approved for public release;
distribution unlimited


Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER ARL-TR-76-31	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Summary of Environmental Acoustic Data Processing	5. TYPE OF REPORT & PERIOD COVERED Annual Report 1 Jul 1973-30 Jun 1974	6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Glen E. Ellis	8. CONTRACT OR GRANT NUMBER(s) N00014-70-A-0166 Task 0016	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Applied Research Laboratories The University of Texas at Austin Austin, Texas 78712	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS	
11. CONTROLLING OFFICE NAME AND ADDRESS Office of Naval Research Department of the Navy Arlington, VA 22217	12. REPORT DATE 5 July 1976	13. NUMBER OF PAGES 24
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	15. SECURITY CLASS. (of this report) Unclassified	16. DECLASSIFICATION/DOWNGRADING SCHEDULE
17. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited		
18. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
19. SUPPLEMENTARY NOTES		
20. KEY WORDS (Continue on reverse side if necessary and identify by Block number) data processing environmental acoustics continuous wave processing explosive source processing ambient noise		
21. ABSTRACT (Continue on reverse side if necessary and identify by Block number) This report summarizes the tasks performed under Contract N00014-70-A-0166, Task 0016, during the period 1 July 1973 through 30 June 1974. Description of the modifications to the continuous wave, ambient noise, and explosive source processing systems is provided. The utilization of these analyses for a "quick look" and volume data processing associated with the BLAKE Test and the CHURCH ANCHOR and the SQUARE DEAL Exercises is described. Other short term analyses and technical support efforts are described.		

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)



Unclassified

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

ARL-TR-76-31
5 July 1976

SUMMARY OF ENVIRONMENTAL ACOUSTIC DATA PROCESSING
Annual Report under Contract N00014-70-A-0166, Task 0016
1 July 1973 - 30 June 1974

Glen E. Ellis

OFFICE OF NAVAL RESEARCH
Contract N00014-70-A-0166, Task 0016

MESSAGE TO	
DTIC	WFO Section <input checked="" type="checkbox"/>
SCC	SW Section <input type="checkbox"/>
UNCLASSIFIED	<input type="checkbox"/>
RESTRICTED	
BY	
DISTRIBUTION AND AVAILABILITY CODES	
CLASS	SPECIAL
A	

APPLIED RESEARCH LABORATORIES
THE UNIVERSITY OF TEXAS AT AUSTIN
AUSTIN, TEXAS 78712

Approved for public release;
distribution unlimited

ABSTRACT

This report summarizes the tasks performed under Contract N00014-70-A-0166, Task 0016, during the period 1 July 1973 through 30 June 1974. Description of the modifications to the continuous wave, ambient noise, and explosive source processing systems is provided. The utilization of these analyses for a "quick look" and volume data processing associated with the BLAKE Test and the CHURCH ANCHOR and the SQUARE DEAL Exercises is described. Other short term analyses and technical support efforts are described.

TABLE OF CONTENTS

	<u>Page</u>
ABSTRACT	iii
I. INTRODUCTION	1
II. DATA PROCESSING SYSTEMS	3
A. SUS Processing System	3
B. Ambient Noise/Continuous Wave Processing System	4
III. DATA PROCESSING	15
A. Data Processing Planning	15
B. "Quick Look" Analyses	15
C. Volume Data Processing	16
IV. ANALYSIS AND REPORTING	17
A. CHURCH ANCHOR Exercise	17
B. SQUARE DEAL Exercise	17
C. SUS Diagnostic Plan	17
D. High Resolution CW Study	17
E. High Resolution Travel Time Measurements of SUS Signals	18
F. SUS Processing Quality Control Study	18
REFERENCES	21

I. INTRODUCTION

The work described in this report was performed under Contract N00014-70-A-0166, Task 0016, during the period 1 July 1973 through 30 June 1974. The areas of work performed were data processing system development and modifications, environmental acoustic data processing and analysis, exercise planning, and technical support. Specifically, tasks in these areas were involved with the BLAKE Test and the CHURCH ANCHOR and the SQUARE DEAL Exercises.

II. DATA PROCESSING SYSTEMS

During this period of work, modifications were made to the explosive source (SUS) processing system to incorporate new features and automate the procedures to handle the large volume of data. The ambient noise/continuous wave processing systems (AN/CW) were redesigned and combined in the implementation.

A. SUS Processing System

Two updates were made to the software portion of the SUS processing system: (1) an algorithm to automatically determine signal length on a shot-to-shot basis and (2) procedures to address the false alarm rate.

The SUS signal duration is independently determined on each data channel (maximum of three) because varying propagation paths can exist between the source and receiving hydrophones. An adaptive filter based on the signal energy relative to the ambient noise energy is used to determine the received shot signal termination. Shot epoch is determined independently on each corresponding data channel.¹ Information from each detected SUS is used to update the filter parameters for each following event.

False alarms using the automation shot detector became a concern during the processing and analysis of the CHURCH ANCHOR SUS data. Although the processing system can require coincident detection on either two or three hydrophone data channels, a procedure to conduct a quality assurance during the postprocessing phase was required. One output of the SUS processor is the high resolution spectra of the SUS signal and ambient noise segment associated with that signal over the frequency band of 10 to 300 Hz.¹ These spectra are archived on digital

tape during processing and can be used to identify the low signal-to-noise ratio (SNR) SUS signals. A criterion was derived to establish a confidence level on the detected SUS signal relative to the SNR. The methods will be reported in the technical report on the SUS diagnostic work.

B. Ambient Noise/Continuous Wave Processing System

The large scale environmental acoustic exercises have generated large volumes of ambient noise (AN) and continuous wave (cw) data. These data are recorded by analog systems from hydrophones distributed throughout the water columns.

The ambient noise/continuous wave processing system (AN/CW) is implemented with a modification of the hardware/software system that has been utilized and updated for the studies of active sonar signal processing. The hardware portion of the system consists of a CDC 3200 digital computer with associated peripherals, including a flexible analog-to-digital (A/D) and digital-to-analog (D/A) interface. The software utilized was based on the routines existing in the signal processing software library for the CDC 3200.

AN/CW Processor Description

The AN/CW processor is a hardware/software configuration designed to perform a narrowband analysis over a variable frequency range by handling large volumes of data. The system is divided into five tasks: A/D conversion, spectral estimation, band estimation, editing, and display. Parameters such as bandwidth, frequency range and resolution, and integration or averaging time can be readily adopted to suit different applications.

For the A/D task, the analog data recordings are time compressed in playback and are converted to digital format. The equipment

configuration is shown in Fig. 1.² One hydrophone channel along with the corresponding timing and receiving system information is digitized on each processing run. Programmable amplifiers, controlled by the digital computer, are used to maximize the dynamic range utilization of the A/D converter. The sampling signal is phased locked to a reference on the data tape or on the time code carrier to minimize errors due to record/playback fluctuations.

During one A/D pass, the computer flags any sample whose amplitude exceeds the range of the A/D converter. The computer also determines the peak and average amplitude of the data for each minute. This information is used to determine the desired amplifier setting for the data in the following minute. Time synchronization checks are maintained by the computer throughout an A/D run.

The second task of the processor is to compute and calibrate a narrowband spectra from contiguous time increments throughout the data period analyzed. Currently, an 8192 point FFT is used to provide a frequency resolution of 0.07 Hz for the frequency range of 10 to 300 Hz.

The ambient noise spectra can be both time averaged over a selected period and output as narrowband and/or octave band time series. Various statistical algorithms are available to furnish the information required to perform an acoustical analysis of the data.

The cw analysis is achieved by using the calibrated narrowband spectra to estimate the signal power in a given frequency band. The spectra are first averaged for a specified period. From these averages, two types of band estimates are obtained. For each cw signal, a narrowband (2 Hz wide) centered about the source frequency is searched for its spectral peak line. The power in a narrower band (0.22 Hz) centered about this peak is then determined. Peak tracking is used to compensate for any Doppler shift and variation in source frequency that might occur.




FIGURE 1
ANALOG EQUIPMENT CONFIGURATION

The third task performed by the AN/CW processor automatically edits the reduced data for artifacts and contamination from the following sources:

1. environmental effects such as biological and seismic noise,
2. exercise effects such as conflicting sources (SUS), source level fluctuations, source timing, and shipping noise, and
3. receiver and recording system effects.

The techniques and algorithms used in the editing phase are software implemented with the exception of some SUS detection accomplished during the A/D phase. These algorithms consist of calibrations, data quality indicators, information from exercise operations, and adaptive filter for octave and narrowband noise estimators, peak tracking, and correction of receiver system artifacts.

The data display consists of graphics and tabulations specified and required in the final analysis performed. Figure 2 summarizes the AN/CW processor.

Processor Outputs

The following outputs of the AN/CW processor are available for analysis:

1. ambient noise spectra in narrow and/or octave bands,
2. cw signal power, noise power, and signal-to-noise or signal excess estimates in narrow frequency bands, and
3. propagation loss (PL), noise power estimates, and signal-to-noise or signal excess estimates versus range and/or time.

Examples of PL and signal excess ($S+N^1/N$) in the deep ocean are shown in Figs. 3 and 4. These plots show the PL along the same track for an inbound source and then for an outbound source. The figures illustrate the repeatability of the PL as a function of range. Equally interesting is that they show rather large variations in the noise

REQUIRED INPUTS

EVENT TIMES + HYDROPHONE
NUMBERS
FREQUENCY RANGE
cw PROCESSING BANDWIDTH
TIMECODE SYNC
CALIBRATION SIGNAL FORMAT
AND LOCATIONS
OVERLOAD SIGNAL FORMAT
HYDROPHONE/TAPE CHANNEL
ASSIGNMENTS
ANALOG TAPE

RECEIVER CONFIGURATION
HYDROPHONE SENSITIVITY
PREAMPLIFIER GAIN AND RESPONSE
CABLE LOSS FOR EACH HYDROPHONE
CALIBRATION SIGNAL LEVELS
ANY PERTINENT PRE/POST
DEPLOYMENT NOTES

SOURCE FREQUENCIES (0.1 Hz)
APPROXIMATE SOURCE SPEED AND
DIRECTION
SOURCE FREQUENCY STABILITY

RANGE AND BEARING TO SOURCE
SOURCE LEVELS AND ON TIMES
SHIPPING PROXIMITY
CONFLICTING EVENTS

RECIPIENTS
FORMATS
AVERAGING TIMES

OUTPUTS

COMPUTER LOG
OPERATOR NOTES
RAW DIGITAL TAPES CONTAINING
DIGITIZED DATA
TIMECODE INFORMATION
AMPLIFIER SETTINGS
OVERLOAD AND CLIPPING
INDICATORS
BOOKKEEPING ENTRIES

CONVERSION FACTORS
OVERALL FREQUENCY RESPONSE
STATISTICS ON RECEIVER
AMPLITUDE STABILITY
FREQUENCY STABILITY
GAIN STATES
NOISE FLOOR
SPECTRA SAVED ON DIGITAL TAPE

PEAKS, MEANS, AND MEDIANS
WITHIN EACH cw BAND
TOTAL POWER IN EACH 1/3 OCTAVE
BAND NORMALIZED TO 1 Hz
HIGH RESOLUTION AVERAGED
SPECTRA
STATISTICS ON RECEIVER AND A/D
ARTIFACTS
INTERMEDIATE DIGITAL TAPES
COMPUTER LOG

FINAL DIGITAL TAPES
EDITING STATISTICS

PLOTS
TABULATIONS
STATISTICS
TRANSMITTAL TAPES



FIGURE 2
ARL/UT AN/CW PROCESSOR FUNCTIONS




FIGURE 3
 cw PROPAGATION LOSS
 ACODAC SYSTEM 1 HYDROPHONE 6 5328 m BOTTOM
 CHAIN TRACK G-F SOURCE J15-3 70 Hz 91 m 157 dB




FIGURE 4
 cw PROPAGATION LOSS
 ACODAC SYSTEM 1 HYDROPHONE 6 5328 m BOTTOM
 CHAIN TRACK F-G SOURCE J15-3 70 Hz 91 m 156 dB

background. Such noise variations are difficult to interpret when viewed through a narrowband processor. ARL has found that a valuable aid in interpretation is a time versus frequency plot of the total available spectrum. For example, the noise increase in Fig. 3 is identified as a moving broadband source in the three-dimensional plot shown in Fig. 5. Another view of Fig. 5 is Fig. 6, which is a better illustration of the quantitative rise in the noise level.




FIGURE 5
NARROWBAND SPECTRA
5328 m BOTTOM
J-15 F TO G VIBROSEIS G TO E

ARL - UT
AS-76-793
OEE - DR
7-14-76




FIGURE 6
TIME VARYING HIGH RESOLUTION SPECTRUM
(AMBIENT NOISE PLUS cw SIGNALS)

III. DATA PROCESSING

The data processing of the environmental acoustic data consisted of data quality assessments, "quick look or response" analyses, and volume data processing of ambient noise, cw, and SUS data for the BLAKE Test, the CHURCH ANCHOR Exercise, and the SQUARE DEAL Exercise.

A. Data Processing Planning

Applied Research Laboratories, The University of Texas at Austin (ARL/UT) participated in the preparation of the CHURCH ANCHOR and the SQUARE DEAL Exercise Data Analysis Plans. Procedures, requirements, and schedules for the data processing together with the interactions and data flow between other exercise participants were developed and documented in a plan to achieve the exercise goals. Technical representatives from ARL/UT attended numerous meetings during this preparation phase. The response of ARL/UT to the data processing task outlined in these plans was via memoranda to the manager of the Long Range Acoustic Propagation Project (LRAPP).

B. "Quick Look" Analyses

"Quick look" analyses were conducted on both CHURCH ANCHOR and SQUARE DEAL environmental acoustic data. These types of analyses were performed to determine the suitability of the data for further processing. These results along with the processing recommendations were furnished to the LRAPP manager and the appropriate exercise technical director via technical memoranda.

A "quick look" analysis similar to the preliminary ACODAC analysis³ was performed in support of the chief scientist for the BLAKE test.

The primary acoustic source of interest was the SUS charges (explosive sources). One objective of the data analysis was to provide information for the investigation of ACODAC cable strumming. The results of this study were provided in an ARL technical memorandum.⁴

C. Volume Data Processing

A large volume of acoustic data was processed for the CHURCH ANCHOR Exercise. The data were recorded on analog tape from the ACODAC and FLIP receivers. The data types included ambient noise, cw, and SUS. The outputs of the data processing, as outlined in the CHURCH ANCHOR Data Analysis Plan, were ambient noise levels, propagation loss, and signal-to-noise ratios throughout the water column. The volume of data processed in hydrophone days (HD) and hydrophone shots (HS) was:

<u>Sensor</u>	<u>Noise (HD)</u>	<u>cw (HD)</u>	<u>SUS (HS)</u>
ACODAC	17	13	21,291
FLIP	--	--	1,935

For the SQUARE DEAL Exercise, a limited volume of SUS data was processed for analysis for the SQUARE DEAL Exercise Synopsis Report issued by the exercise technical director.

IV. ANALYSIS AND REPORTING

A. CHURCH ANCHOR Exercise

ARL/UT participated with staff members from Texas Instruments, Inc., (TI) in the analysis and documentation of the ambient noise and cw data. Technical reports were issued by TI. The analysis of the SUS data was performed by ARL/UT and will be documented in technical report form. ARL/UT also assisted the chief scientist in the preparation of the Environmental Acoustic Summary Report.

B. SQUARE DEAL Exercise

A summary of the preliminary findings from the limited amount of the processed SUS data for the SQUARE DEAL Exercise Synopsis Report was submitted to the technical director.

C. SUS Diagnostic Plan

ARL/UT participated in the planning of the SUS diagnostic plan that addresses the consistency aspects of SUS data processing within the organizations participating in the LRAPP data processing program. The efforts outlined in the plan have been initiated by using a selected data set from a SQUARE DEAL Exercise ACODAC. ARL/UT is coordinating the data processing and will assist Underwater Systems, Inc., in the analysis and interpretation of the results. A technical report will provide the documentation for these results.

D. High Resolution cw Study

ARL/UT participated in a LRAPP sponsored meeting concerning high resolution cw data processing. The emphasis of the meeting was to

coordinate the processor parameters used by the various participants in the data analysis of the environmental acoustics collected during the LRAPP sponsored exercises. As a result of this meeting, ARL/UT was requested to perform a high resolution frequency analysis on related data sets to determine the presence of observable sidebands in cw signals generated by a moving source and received at ranges of up to 200 nm in the deep ocean. Theoretical predictions, as well as observations at relatively short ranges, and steep grazing angles show that a sound wave which is forward scattered from the ocean surface has its frequency components smeared by surface wave motions. The results of this analysis will be forwarded to the LRAPP manager in a technical memorandum.

E. High Resolution Travel Time Measurements of SUS Signals

During the CHURCH ANCHOR and SQUARE DEAL Exercises, the positions of the receivers at deployment and of source ships during their runs were determined from satellite fixes. There was some concern over the possibility of large errors (on the order of several nautical miles) in source-to-receiver ranges because of ineffective interpolation along the source track. The signal travel times are available as a byproduct of the ARL SUS processing; these times were examined for possible discrepancies between the acoustic information and the navigation data. Once the pattern of the acoustic data was explained, the accuracy of the navigation data was seen to be better than 0.1 nm. However, the travel time measurements are interesting in themselves. They were seen to reflect the sound velocity structure of the medium and also to give some indication of the variability of propagation loss to be expected. The results of this study were provided to the LRAPP manager in memorandum form.

F. SUS Processing Quality Control Study

The errors associated with the analysis of signals from explosive sources have been analyzed and reported. The effects of analog

reproduction and subsequent digital conversion of the data on the estimation of propagation loss were considered. In addition, the techniques of spectral analysis as applied to these impulsive type data were addressed. The work was documented in an ARL technical memorandum.⁵

In summary, it was found that the digitizing processing can be repeated on a day-to-day basis to the extent that the energy in frequency bands for either shots or noise has standard deviations of 1 to 2%. The times at which the automatic SUS processor detected a shot showed no fluctuations other than those to be expected from the temporal resolution imposed by the sampling rate. The standard deviations due to repeated processing of transmission loss for a given frequency band is of the order of 0.1 to 0.2 dB.

REFERENCES

1. G. E. Ellis, "Summary of Environmental Acoustic Data Processing," Applied Research Laboratories Technical Report No. 75-32 (ARL-TR-75-32), Applied Research Laboratories, The University of Texas at Austin, 10 June 1975.
2. R. O. Grohman, L. L. Mellenbruch, and F. J. Sawicki, "Special Hardware For ARL ACODAC Data," Applied Research Laboratories Technical Memorandum No. 74-12 (ARL-TM-74-12), Applied Research Laboratories, The University of Texas at Austin, 14 March 1974.
3. G. E. Ellis, T. D. Plemons, L. D. Hampton, and J. A. Shooter, "ARL Preliminary Data Analysis From ACODAC System," Applied Research Laboratories Technical Memorandum No. 73-11 (ARL-TM-73-11), Applied Research Laboratories, The University of Texas at Austin, 20 July 1973.
4. G. E. Ellis, T. D. Plemons, L. D. Hampton, and J. A. Shooter, "Analysis of the BLAKE Test ACODAC Data," Applied Research Laboratories Technical Memorandum No. 73-12 (ARL-TM-73-12), Applied Research Laboratories, The University of Texas at Austin, 20 July 1973.
5. S. F. Mitchell and T. D. Plemons, "Quality Control Analysis of SUS Processing From ACODAC Data," Applied Research Laboratories Technical Memorandum No. 73-42 (ARL-TM-73-42), Applied Research Laboratories, The University of Texas at Austin, 20 December 1973.

14 July 1976

DISTRIBUTION LIST FOR
 ARL-TR-76-31
 ANNUAL REPORT UNDER CONTRACT N00014-70-A-0166, Task 0016
 UNCLASSIFIED

Copy No.

1 - 3	Office of Naval Research Department of the Navy Arlington, VA 22217 Attn: Code 480
4	Code 460
5	Code 102-OS
6 - 11	Code 105
12	Office of Naval Research Branch Office Chicago 536 South Clark Chicago, IL 60605
13	Office of Defense Research and Engineering Office of the Secretary of Defense Washington, DC 20301 Attn: Office, Assistant Director (Research)
14 - 19	Director Naval Research Laboratory Washington, DC 20375 Attn: Library, Code 2620
20	Commander Naval Oceanographic Office Department of the Navy Washington, DC 20390 Attn: Code 1640
21	Code 70
22	National Oceanic Atmospheric Administration (NODC/NOAA) Rockville, MD 20882
23 - 34	Commanding Officer and Director Defense Documentation Center Defense Services Administration Cameron Station, Building 5 5010 Duke Street Alexandria, VA 22314

Distribution List for ARL-TR-76-31, N00014-70-A-0166, Task 0016 (Cont'd)

Copy No.

- | | |
|----|------------------------------------------------------------------------------------------------------------------------------|
| 35 | Office of Naval Research
Resident Representative
Room 582, Federal Building
300 East 8th Street
Austin, TX 78701 |
| 36 | Computer Sciences Division, ARL/UT |
| 37 | Marine Sciences Division, ARL/UT |
| 38 | Reuben H. Wallace, ARL/UT |
| 39 | Library, ARL/UT |



DEPARTMENT OF THE NAVY

OFFICE OF NAVAL RESEARCH
875 NORTH RANDOLPH STREET
SUITE 1425
ARLINGTON VA 22203-1995

IN REPLY REFER TO:

5510/1
Ser 321OA/011/06
31 Jan 06

MEMORANDUM FOR DISTRIBUTION LIST

Subj: DECLASSIFICATION OF LONG RANGE ACOUSTIC PROPAGATION PROJECT
(LRAPP) DOCUMENTS

Ref: (a) SECNAVINST 5510.36

Encl: (1) List of DECLASSIFIED LRAPP Documents

1. In accordance with reference (a), a declassification review has been conducted on a number of classified LRAPP documents.
2. The LRAPP documents listed in enclosure (1) have been downgraded to UNCLASSIFIED and have been approved for public release. These documents should be remarked as follows:

Classification changed to UNCLASSIFIED by authority of the Chief of Naval Operations (N772) letter N772A/6U875630, 20 January 2006.

DISTRIBUTION STATEMENT A: Approved for Public Release; Distribution is unlimited.

3. Questions may be directed to the undersigned on (703) 696-4619, DSN 426-4619.

BRIAN LINK
By direction

Subj: DECLASSIFICATION OF LONG RANGE ACOUSTIC PROPAGATION PROJECT
(LRAPP) DOCUMENTS

DISTRIBUTION LIST:

NAVOCEANO (Code N121LC – Jaime Ratliff)
NRL Washington (Code 5596.3 – Mary Templeman)
PEO LMW Det San Diego (PMS 181)
DTIC-OCQ (Larry Downing)
ARL, U of Texas
Blue Sea Corporation (Dr. Roy Gaul)
ONR 32B (CAPT Paul Stewart)
ONR 321OA (Dr. Ellen Livingston)
APL, U of Washington
APL, Johns Hopkins University
ARL, Penn State University
MPL of Scripps Institution of Oceanography
WHOI
NAVSEA
NAVAIR
NUWC
SAIC

Declassified LRAPP Documents

Report Number	Personal Author	Title	Publication Source (Originator)	Pub. Date	Current Availability	Class.
55	Weinstein, M. S., et al.	SUS QUALITY ASSESSMENT, SQUARE DEAL	Undersea Systems, Inc.	750207	ADA007559; ND	U
BKD2380	Unavailable	WESTLANT 74 PHASE 1 DATA SUMMARY (U)	B-K Dynamics, Inc.	750301	NS; ND	U
TM-SA23-C44-75	Wilcox, J. D.	MOTION MODEL VALIDATION FROM LRAPP ATLANTIC TEST BED DATA	Naval Underwater Systems Center	750317	ND	U
RAFF7412; 74-482	Scheu, J. E.	SQUARE DEAL SHIPPING DENSITIES (U)	Raff Associates, Inc.	750401	ADC003198; NS; ND	U
PSI TR-004018	Barnes, A. E., et al.	ON THE ESTIMATION OF SHIPPING DENSITIES FROM OBSERVED DATA	Planning Systems Inc.	750401	AD 096 582	U
NUSC TD No.4937	LaPlante, R. F., et al.	THE MOORED ACOUSTIC BUOY SYSTEM (MABS)	Naval Underwater Systems Center	750404	ADB003783; ND	U
USI 460-1-75	Weinstein, M. S., et al.	SUS SIGNAL DATA PROCESSING (U) INVESTIGATIONS CONDUCTED UNDER THE DIAGNOSTIC PLAN FOR CHURCH ANCHOR AND SQUARE DEAL SHOT DATA (U)	Underwater Systems, Inc.	750414	ADC002353; ND	U
Unavailable	Ellis, G. E.	SUMMARY OF ENVIRONMENTAL ACOUSTIC DATA PROCESSING	University of Texas, Applied Research Laboratories	750618	ADA011836	U
Unavailable	Edelblute, D. J.	OCEANOGRAPHIC MEASUREMENT SYSTEM TEST AT SANTA CRUZ ACOUSTIC RANGE FACILITY (SCARF)	Lockheed Missiles and Space Co., Inc.	751015	ADB007190	U
Unavailable	Unavailable	SUS SOURCE LEVEL COMMITTEE REPORT	Underwater Systems, Inc.	751105	ADA019469	U
Unavailable	Hampton, L. D.	ACOUSTIC BOTTOM INTERACTION EXPERIMENT DESCRIPTION	University of Texas, Applied Research Laboratories	760102	ADA021330	U
PSI-TR-036030	Turk, L. A., et al.	CHURCH ANCHOR: AREA ASSESSMENT FOR TOWED ARRAYS (U)	Planning Systems Inc.	760301	ND	U
NUC TP 419	Wagstaff, R. A., et al.	HORIZONTAL DIRECTIONALITY OF AMBIENT SEA NOISE IN THE NORTH PACIFIC OCEAN (U)	Naval Undersea Center	760501	ADC007023; NS; ND	U
NRL-MR-3316	Young, A. M., et al.	AN ACOUSTIC MONITORING SYSTEMS FOR THE VIBROSEIS LOW-FREQUENCY UNDERWATER ACOUSTIC SOURCE	Naval Research Laboratory	760601	ADA028239; ND	U
ARL-TR-75-32	Ellis, G. E.	SUMMARY OF ENVIRONMENTAL ACOUSTIC DATA PROCESSING	University of Texas, Applied Research Laboratories	760705	ADA028084; ND	U
Unavailable	Unavailable	SUMMARY OF ENVIRONMENTAL ACOUSTIC DATA PROCESSING	University of Texas, Computer Science Division	761013	ADA032562	U
TTA83676285	Unavailable	ANALYSIS PLAN FOR NARROWBAND/ NARROWBEAM AMBIENT NOISE (U)	Tetra Tech, Inc.	761112	ADC008275; NS; ND	U
USI 564-1-77	Wallace, W. E., et al.	REPORT OF CW WORKSHOP. NORDA, BAY ST. LOUIS, MISS., 28-29 SEPT 1976	Underwater Systems, Inc.	770124	ND	U